

DESCRIPTION

Black Swan's Stay Soft Plumbers Putty is a special formulated putty which will stay soft and flexible and will not shrink, bleed, harden, crack or crumble. It is gas proof, odor proof and water resistant.

Black Swan's Stay Soft Plumbers Putty can be used for setting toilet bowls, fixtures, faucets, strainers, basin cocks, sink frames, and many other sealing and caulking applications.

Stay Soft Plumbers Putty is a stainless putty and meets Federal Specification TT-P-1536A.

WHAT DOES "STAINLESS" MEAN?

The word stainless refers to how the oil in the putty bleeds from the putty when it comes into contact with other material. For example, the oil in an inexpensive putty will bleed easily and stain whatever surface it comes into contact with. A higher quality putty will hold the oil better and not cause a stain.

The word stainless does not refer to stainless steel putty.

DIRECTIONS

- 1. Apply Stay Soft Plumbers Putty liberally and evenly to clean dry surface.
- 2. Set and tighten fixture.
- 3. Remove excess putty.

FOR NATURAL MARBLE SURFACE

1. Do not let putty come into contact with natural marble surface.

- 2. Brush or spray marble area with clear acrylic lacquer. Allow to dry.
- 3. Apply putty as noted above.

CAUTIONS

Keep out of reach of children. Do not take internally. Contents are toxic.

UPC NUMBER AND CARTON INFORMATION

STOCK NO.	SIZE	UPC NUMBER	CARTON CUBIC FEET
01037	7 oz.	0 54647 01037 3	.210
01040	14 oz.	0 54647 01040 3	.355
01041	28 oz.	0 54647 01041 0	.371
01043	3 lb.	0 54647 01043 4	.773
01045	5 lb.	0 54647 01045 8	.568
01047	7 lb.	0 54647 01047 2	.708
01050	15 lb.	0 54647 01050 2	.776
01055	25 lb.	0 54647 01055 7	.509
01060	50 lb.	0 54647 01060 1	1.000
01062	75 lb.	0 54647 01062 5	1.375
01065	450 lb.	0 54647 01065 6	8.25